

For a perfect
joint

More information
from specialist suppliers

Weather-resistant sealing
in building construction

Tools and accessories

**Professional products
for perfect jointing all
from one supplier:**

Cleaner

Primer

PE-Back-up Foam Rod

Hand-operated Guns

Smoothing Agent

Scraper



Hand-operated Guns



Scraper



Cleaner



Smoothing Agent



Primer



PE-Back-up Foam Rod

Supplier's stamp

Index: 9999439-GB-01.01.2017
© Hermann Otto GmbH 2017

Notes:
The information in the present document corresponds to the status quo on going to print, refer to the index. With a new edition this edition becomes invalid. Due to the many possible influences during and after application, the customer always has to carry out trials first. Please observe the respective technical data sheet! This information is available on the Internet at www.otto-chemie.com. Errors and typographical errors are excepted.

Find out about the other OTTO products for sealing and bonding at www.otto-chemie.com



Sealants • Adhesives

Hermann Otto GmbH · Krankenhausstr. 14 · 83413 Fridolfing, GERMANY

Tel.: 0049-8684-908-0 · Fax: 0049-8684-1260

E-Mail info@otto-chemie.de · www.otto-chemie.com

**Hybrid sealant according to
DIN EN ISO 11600 F 25 LM**



Sealants • Adhesives

Hybrid

for the expansion joint

OTTOSEAL® M 360

The hybrid sealant for expansion joints in building construction according to DIN 18540-F and the new European norm DIN EN ISO 11600 F 25 LM does neither contain isocyanates and silicones nor solvating agents.

OTTOSEAL® M 360 is also perfectly suitable for applications within the scope of the IVD-Instruction sheets no. 7 “Elastic Joint Seals in Facades of Ceramic Tiles fixed with mortar” and no. 9 “Extrudable sealants in the joints around windows and front doors”.



The most important features at a glance

Characteristics:

- 1-component sealant based on silane-terminated polymers (hybrid)
- Compatible with coatings according to DIN 52452
- Good weathering and ageing resistance
- Cures without bubble formation
- Low odour
- Free of isocyanates
- Silicone-free
- Stress expansion modulus at 100 % (DIN 53 504, S3A): 0,4 N/mm²

Fields of application:

- External joints according to DIN 18540-F
- Sealing of joints on façades, metal constructions
- Expansion joints on prefabricated concrete and cellular concrete units
- Bonding of OTTO Window Tapes BAB/A and BAB/I on masonry, concrete, cellular concrete etc.

Standards and tests:

- Tested according to EN 15651 – Part 1: F EXT-INT CC 25 LM
- Tested according to DIN EN ISO 11600 F 25 LM (ift Rosenheim, germany)
- Suitable for applications according to IVD instruction sheet no. 7+9+12+19-1+20+22+24+27+29+31+32+35 (IVD = German industry association sealants)
- Quality seal of the IVD (Industrial association for sealants, registered society), tested by the ift Rosenheim (Institute of window engineering, registered society)
- According to regulation (EG) Nr. 1907/2006 (REACH)
- Conform to LEED® v3 IEQ-credits 4.1 adhesives and sealants
- For DGNB classifications, see the product page on the OTTO website
- French VOC-emission class A+
- Declaration in “baubook” Austria