


OTTOSEAL® S 100



	
757	
Hermann Otto GmbH Krankenhausstr. 14, 83413 Fridolfing, Germany 2014 OC0100B	
EN 15651 - 1, EN 15651 - 2 EN 15651 - 3, EN 15651 - 4 1-component silicone sealant, acetate curing for application in the facade for glazing for application in the sanitary area for pedestrian walkways - Type F EXT-INT CC, G CC, S, PW INT - Conditioning: Process A - Carrier material: glass - Pretreatment: OTTO Cleanprimer 1226	
Fire behaviour	Class E
Release of chemicals hazardous to health and/or the environment	evaluated
Water- and airtightness	
a) Tensile behaviour under pretensioning	passed (NF)
b) Stability under load	≤ 3 mm
c) Volume loss	≤ 10 %
d) Tearing strength	passed (NF)
e) Tensile behaviour, i.e. stress expansion under pretensioning after submersion in water	passed (NF)
f) Adhesive/stress expansion action after the effects of heat, water and artificial light	passed (NF)
g) Resilience	≥ 70 %
h) Tensile properties / secant modulus in cold climate (at -30°C)	≤ 0.9 MPa
i) Tensile properties under pretensioning in a cold climate (at -30°C)	passed (NF)
j) Microbiological growth	0
Durability	passed (NF)