Printing date 06.05.2015 Revision: 06.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: OTTOSEAL S 72

· Application of the substance / the mixture Silicone sealant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Hermann Otto GmbH Krankenhausstraße 14 D-83413 Fridolfing Tel.: 0049/(0)8684/908-0 Fax.: 0049/(0)8684/908-539

· Further information obtainable from:

Tel.: 0049- (0)8684- 908- 641 (-460) E-Mail: alois.parzinger@otto-chemie.de

• 1.4 Emergency telephone number: Tel.: 0049- (0)89- 192 40 (emergency telephone no.)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC not applicable
- Information concerning particular hazards for human and environment:

The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Ensure good ventilation during application and curing.

Contains 3-aminopropyltriethoxysilane. May produce an allergic reaction.

Safety data sheet available on request.

· 2.3 Other hazards

During the application and curing process of the material chemicals are released as vapour (see item 11). Therefore ensure good ventilation or exhaustion if necessary.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Polydimethylsiloxane, filler, auxiliaries, alkoxy crosslinker
- Dangerous components:

CAS: 1185-55-3 trimethoxy(methyl)silane

EINECS: 214-685-0 F R11

Tlam. Lig. 2, H225

< 5%

(Contd. on page 2)

Printing date 06.05.2015 Revision: 06.05.2015

Trade name: OTTOSEAL S 72

(Contd. of page 1)

CAS: 128446-60-6 Silsesquioxanes, 3-aminopropyl Me, ethoxy-terminated

< 5%

🗶 Xi R36/38

🚸 Flam. Liq. 3, H226; 伙 Skin Irrit. 2, H315; Eye Irrit. 2, H319

· Additional information For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· After skin contact

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing

Do not induce vomiting; call for medical help immediately. Show container or label. Rinse out mouth and then drink plenty of water in small amounts (if person is conscious).

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Mount respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

see item 8: Personal protective equipment

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 3)

Printing date 06.05.2015 Revision: 06.05.2015

Trade name: OTTOSEAL S 72

Protect from heat and direct sunlight.

(Contd. of page 2)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
- CAS No. Designation of material % Type Value Unit
- Additional Occupational Exposure Limit Values for possible hazards during processing:

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

Sk

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment
- General protective and hygienic measures

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e.type ABEK according to standard EN 14387) is used.

- · Protection of hands: Protective gloves.
- · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR Natural rubber, NR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Safety glasses
- · Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: pasty

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.

· Change in condition

Melting point/Melting range: undetermined Boiling point/Boiling range: undetermined

• Flash point: undetermined

· **Self-igniting:** Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Density at 20 °C: 1.02 g/cm³

(Contd. on page 4)

Printing date 06.05.2015 Revision: 06.05.2015

Trade name: OTTOSEAL S 72

(Contd. of page 3)

· Solubility in / Miscibility with

Water: Insoluble

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Avoid strong heating.

· 10.6 Hazardous decomposition products:

Tests on representative products have shown that above temperatures of 150 °C small quantities of formaldehyde are split off.

see item 5.2

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritating effects to skin and mucous membranes possible
- · on the eye: Irritating effect possible
- Other information (about experimental toxicology):

Product hydrolyses under formation of methanol (CAS no. 67-56-1). Methanol is toxic by inhalation, in contact with skin and if swallowed. Methanol causes damage to organs. Methanol is highly flammable. Inhalation of aerosol spray may damage health.

SECTION 12: Ecological information

- · 12.2 Persistence and degradability
- · Other information: Product is not biodegradable.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Observe local by-laws.

Already cured material can be disposed of with the domestic or commercial waste. Unconsumed material (fluid, paste-like) is to dispose of as hazardous waste.

- · Uncleaned packaging:
- · Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

GB

Printing date 06.05.2015 Revision: 06.05.2015

Trade name: OTTOSEAL S 72

(Contd. of page 4)

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

14.7 Transport in bulk according to Annex II

of MARPOL73/78 and the IBC Code Not applicable.

• Transport/Additional information: Not dangerous according to the above

specifications.

UN "Model Regulation":

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Details of international registration status:

Listed on or in accordance with the following inventories:

EINECS - Europe listed AICS - Australia listed DSL/NDSL - Canada not listed IECSC - China listed ENCS - Japan listed NZIoC - New Zealand not listed PICCS - Philippines listed ECL/KECI - Korea listed TSCA - USA listed NECI - Taiwan not listed

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

R10 Flammable.

R11 Highly flammable.

R36/38 Irritating to eyes and skin.

- · Department issuing MSDS: Tel.: 0049- (0)8684- 908- 641
- · Contact: Tel.: 0049- (0)8684- 908- 641 (-460)

(Contd. on page 6)

Printing date 06.05.2015 Revision: 06.05.2015

Trade name: OTTOSEAL S 72

· Abbreviations and acronyms:

(Contd. of page 5)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

* Data compared to the previous version altered.